

Faxe Combicolor

The colors are in white, black, grey, rosewood, palisander and in mahogany.

Product description:

Faxe Combicolor is a mineral pigment based color concentrate. All Faxe oils, lyes and panel lyes can be colored to meet individual requirements using Faxe Combicolor. Color finishes to oak, beech, ash, pine, spruce and larch look particularly attractive.

Tools:

Paint bucket, stirring rod, metal container if required

Preparation:

Min. processing temperature 18°C.

Application:

- Pour approx. half of the 2.5 l of oil into a paint bucket. Shake 1 can of Faxe Combicolor vigorously and pour the complete contents into the paint bucket. Mix thoroughly using the mixing rod. Pour the remaining oil into the bucket, whilst stirring continuously.
- The oil is now ready for use and can be applied in the same way as described for oil.

Aftercare:

Refer to the label on the product, with which the Combicolor was mixed. Lye colored with Combicolor does not contain a binding agent. The surface of wood treated with this must be oiled, waxed or sealed.

Technical Data:

Usage: Mixing proportion - up to 10%

Cleaning: Clean tools with Faxe Oil Thinner

Drying: Drying will be delayed if there is a large proportion of Combicolor in the oil.

Components:

Mineral pigments in propylene-glycol

Keep under lock and key and out of reach to children

Updated: January 2016

