

# Safety Data Sheet

## FAXE Maintenance Oil 0245

Replaces date: 27/03/2015

Revision date: 03/07/2015  
Version: 4.0.0

### SECTION 1: Identification of the substance/preparation and of the company/undertaking

#### 1.1. Product identifier

**Trade name:** FAXE Maintenance Oil 0245

#### Article no

Article no	Description
0245	

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended uses:** Oil treatment of wood.

**Inadvisable uses:** The product is recommended for only the above described uses.

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

**Company:** Esbjerg Farve- & Lakfabrik A/S

**Address:** Energivej 13

**Zip code:** DK-6700

**City:** Esbjerg

**Country:** DENMARK

**E-mail:** info@esbjergpaints.dk

**Phone:** 0045 75 12 86 00

**Fax:** 0045 75 45 33 68

**Homepage:** www.esbjergpaints.dk

#### 1.4. Emergency Telephone Number

GB: +44 1215074123 (Advice and guidance ) (Around the clock)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**CLP-classification:** Aquatic Chronic 4;H413

**Most serious harmful effects:** May cause long lasting harmful effects to aquatic life.

#### 2.2. Label elements

##### H-phrases

H413 May cause long lasting harmful effects to aquatic life.

##### P-phrases

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance to local regulations.

# Safety Data Sheet

## FAXE Maintenance Oil 0245

Replaces date: 27/03/2015

Revision date: 03/07/2015

Version: 4.0.0

P280 Wear protective gloves.

### Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

**VOC:** This product contains a maximum of 273 g VOC/L. The limit value is 500 g VOC/L (cat. A/i)

### 2.3. Other hazards

The product does not contain any PBT or vPvB substances.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Substance	CAS number	EC No	REACH Reg. No.	Concentration	Notes	CLP-classification
2-methyldecane	90622-57-4	918-167-1	01-2119472146-39	25 - 50%		Flam. Liq. 3;H226 Asp. Tox. 1;H304 Aquatic Chronic 4;H413
Hydrocarbons, C14-C18 n-alkanes, isoalkanes, cyclic compounds, <2% aromatics		927-632-8	01-2119457736-27	25 - 50%		Asp. Tox. 1;H304
2-ethylhexanoic acid, zirconium salt	22464-99-9	245-018-1	01-2119979088-21	< 0.2%		Repr. 2;H361d

Please see section 16 for the full text of H-phrases.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- Inhalation:** If patient feels unwell move to fresh air and keep under surveillance. If the victim is unconscious, ascertain whether the victim is breathing. If breathing has stopped, apply artificial respiration. If the victim is unconscious but breathing, place in the recovery position and keep warm with blankets. Call for medical attention or ambulance.
- Ingestion:** Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention immediately!
- Skin contact:** Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Do not use solvents.
- Eye contact:** Flush immediately with lukewarm water (preferably using eye wash equipment) for at least 15 minutes. Open eye wide. Remove any contact lenses. Seek medical advice.
- General:** If in doubt, seek medical advice. Also see para. 1

### 4.2. Most important symptoms and effects, both acute and delayed

Headache, dizziness, drowsiness and nausea. May cause chemical pneumonia if vomiting.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Fire-fighting measures

# Safety Data Sheet

## FAXE Maintenance Oil 0245

Replaces date: 27/03/2015

Revision date: 03/07/2015  
Version: 4.0.0

### 5.1. Extinguishing media

**Suitable extinguishing media:** Fire can be extinguished with carbon dioxide, powder, foam or water spray.

**Unsuitable extinguishing media:** Do not use a direct water jet that could spread the fire.

### 5.2. Special hazards arising from the substance or mixture

No specific.

### 5.3. Advice for fire-fighters

Cool closed containers with water. Fire will produce a thick black smoke. Products of combustion are harmful and respiratory protection is required.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel:** Avoid inhalation of vapours. Remove all ignition sources and ensure sufficient ventilation. In case of accident use air-supplied respirators and nitrile gloves.

**For emergency responders:** Use nitrile protection gloves and self-contained breathing apparatus.

### 6.2. Environmental precautions

Notify proper authorities in case of contamination of soil or aquatic environment or discharge to drains.

### 6.3. Methods and material for containment and cleaning up

Prevent major quantities of spillage from being discharged into the sewage system or water by banking the spillage with sand or the like and collecting it. Clean the contaminated area with a suitable cleaning agent, but do not use solvent.

### 6.4. Reference to other sections

Also see item 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid contact with eyes and skin. Avoid inhaling vapors and spray mists. Personal protective equipment: Refer to section 8. Do not eat, drink, smoke or store tobacco, food or drink in work places or areas where there is a risk of contact with the product.

Contains drying oils. Risk of self-ignition. After spills and used cloths, etc. have been recovered, store in fireproof waste disposal containers before destroying.

### 7.2. Conditions for safe storage, including any incompatibilities

The product must be kept away from children. Store in a tightly closed container and in accordance with the current regulations in a dry and well-ventilated place away from food. Contains drying oils. Risk of self-ignition. After spills and used cloths, etc. have been recovered, store in fireproof waste disposal containers before destroying.

### 7.3. Specific end use(s)

Applications is mentioned in item 1.2.

# Safety Data Sheet

## FAXE Maintenance Oil 0245

Replaces date: 27/03/2015

Revision date: 03/07/2015  
Version: 4.0.0

**Other Information:** Smoking and the consumption of food and drink are not permitted in work rooms. Personal protective equipment: Refer to section 8.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limit

Substance name	Time period	ppm	mg/m <sup>3</sup>	fiber/cm <sup>3</sup>	Comments	Remarks
Hydrocarbons, C14-C18 n-alkanes, isoalkanes, cyclic compounds, <2% aromatics	15m					
Hydrocarbons, C14-C18 n-alkanes, isoalkanes, cyclic compounds, <2% aromatics	8h	25	180			
2-ethylhexanoic acid, zirconium salt	15m		10		Zr	
2-ethylhexanoic acid, zirconium salt	8h		5		Zr	

**Legal basis:** EH40/2005 Workplace exposure limits incl. supplement from October 2007.

#### PNEC

2-ethylhexanoic acid, zirconium salt				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
Freshwater	0,36 mg/l			
Marine water	0,036 mg/l			
Freshwater - sediment	6,37 mg/kg			
Marine water - sediment	0,637 mg/kg			
Soil	1,06 mg/kg			

#### DNEL - workers

2-ethylhexanoic acid, zirconium salt					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Inhalation	32,97 mg/m <sup>3</sup>	Long-term exposure		Systemic effects	
Dermal	6,49 mg/kg	Long-term exposure		Systemic effects	

#### DNEL - general population

2-ethylhexanoic acid, zirconium salt					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Oral	4,51 mg/kg bw/day	Long-term exposure		Systemic effects	
Inhalation	8,13 mg/m <sup>3</sup>	Long-term exposure		Systemic effects	

# Safety Data Sheet

## FAXE Maintenance Oil 0245

Replaces date: 27/03/2015

Revision date: 03/07/2015

Version: 4.0.0

Dermal	3,25 mg/kg bw/day	Long-term exposure		Systemic effects	
--------	-------------------	--------------------	--	------------------	--

**Biological threshold values:** DNEL - Values are missing. PNEC - Values are missing.

### 8.2. Exposure controls

**Appropriate engineering controls:** All work must be planned with a view to limit the breathing of fumes and the exposure to the skin. If this is not possible, use respiratory protection.

**Personal protective equipment, eye/face protection:** No special precautions required.

**Personal protective equipment, skin protection:** If possible, wear special work clothes. When spraying wear coveralls.

**Personal protective equipment, hand protection:** Use nitrile protection gloves. A 15-mil thickness glove provides a 8 hour breakthrough-time. Follow the glove manufacturer's recommendations on use and replacement.

**Personal protective equipment, respiratory protection:** With insufficient ventilation use respirator with filter type A.

**Environmental exposure controls:** It must be ensured that local regulations for discharge are met.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Parameter	Value/unit
State	Liquid.
Colour	Different.
Odour	Odour of organic solvent.
Solubility	Not miscible with water.
Explosive properties	No information available
Oxidising properties	No information available

Parameter	Value/unit	Remarks
pH (solution for use)	No data	
pH (concentrate)	No data	
Melting point	No data	
Freezing point	No data	
Initial boiling point and boiling range	No data	
Flash Point	> 62	
Evaporation rate	No data	
Flammability (solid, gas)		Irrelevant
Flammability limits		Irrelevant
Explosion limits	0.50 - 7 vol%	
Vapour pressure	No data	
Vapour density	No data	
Relative density	No data	
Partition coefficient n-octanol/water	No data	
Auto-ignition temperature	No data	
Decomposition temperature	No data	
Viscosity	28 - 32 Sec. 4 mm cup	
Odour threshold	No data	

### 9.2 Other information

Parameter	Value/unit	Remarks
-----------	------------	---------

# Safety Data Sheet

## FAXE Maintenance Oil 0245

Replaces date: 27/03/2015

Revision date: 03/07/2015

Version: 4.0.0

Density	0.88 - 0,95 g/cm <sup>3</sup>	
Fire class	III-1	
Weight % organic solvents	31	
VOC	273 g/l	

**Other Information:** Solubility in water: Insoluble in water. Fat solubility: irrelevant

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No information is available.

#### 10.2. Chemical stability

Stable under recommended storage and handling conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reaction known by normal use and normal conditions.

#### 10.4. Conditions to avoid

Heat, flames and sparks. Direct sources of heat. Strong sunlight for prolonged periods.

#### 10.5. Incompatible materials

To prevent heat-generating reactions, keep the product away from oxidizing agents and strong acidic and basic substances.

#### 10.6. Hazardous decomposition products

carbon monoxide.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity - oral

##### Hydrocarbons, C14-C18 n-alkanes, isoalkanes, cyclic compounds, <2% aromatics

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		> 5000mg/kg			

##### 2-methyldecane

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		> 5000mg/kg			

Ingestion of large quantities may cause gastrointestinal disorders.

##### Acute toxicity - dermal

##### Hydrocarbons, C14-C18 n-alkanes, isoalkanes, cyclic compounds, <2% aromatics

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		> 3160mg/kg			

##### 2-methyldecane

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		> 5000mg/kg		OECD 402	

# Safety Data Sheet

## FAXE Maintenance Oil 0245

Replaces date: 27/03/2015

Revision date: 03/07/2015  
Version: 4.0.0

Organic solvents have a degreasing effect on the skin.

### Acute toxicity - inhalation

#### Hydrocarbons, C14-C18 n-alkanes, isoalkanes, cyclic compounds, <2% aromatics

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LC50	4 h	> 5000mg/m <sup>3</sup>			

Inhalation of vapors may cause symptoms of poisoning such as memory and concentration difficulties, abnormal tiredness, irritability and, in extreme cases, unconsciousness.

**Skin corrosion/irritation:** Prolonged or repeated skin contact will degrease skin and may cause irritation.

**Serious eye damage/eye irritation:** Splashing into eyes may cause smarting/irritation.

**Germ cell mutagenicity:** Would not be expected germ cell mutagen

**Carcinogenic properties:** No information available

**Reproductive toxicity:** Would not be expected to be a reproductive toxicant.

**Single STOT exposure:** May cause drowsiness or dizziness.

**Aspiration hazard:** May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Hydrocarbons, C14-C18 n-alkanes, isoalkanes, cyclic compounds, <2% aromatics

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Acute fish		96 h	LL50	> 1028mg/l			
Acute Daphnia		48 h	EL50	> 3193mg/l			
Acute algae	Skeletonema costatum	72 h	NOELR	3198mg/l			
Acute algae	Skeletonema costatum	72 h	EL50	> 3198mg/l			

#### 2-methyldecane

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Acute fish	Onchorhynchus mykiss	96 h	LL0	1000mg/l			
Acute algae	Pseudokirchneriella subcapitata	72 h	ELO	1000mg/l			
Acute algae	Pseudokirchneriella subcapitata	72 h	NOELR	1000mg/l			
Acute Daphnia	Daphnia magna	21 d		0.011mg/l			
Acute daphnia	Daphnia magna	48 h	ELO	1000mg/l			

No information available

### 12.2. Persistence and degradability

# Safety Data Sheet

## FAXE Maintenance Oil 0245

Replaces date: 27/03/2015

Revision date: 03/07/2015

Version: 4.0.0

### Hydrocarbons, C14-C18 n-alkanes, isoalkanes, cyclic compounds, <2% aromatics

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
		28 d		74 %			

### 2-methyldecane

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
		28 d		31.3%			

No information available

### 12.3. Bioaccumulative potential

No information available

### 12.4. Mobility in soil

The product is insoluble in water and will spread out on the surface.

### 12.5. Results of PBT and vPvB assessment

This product is not a substance which is a PBT or vPBT.

### 12.6. Other adverse effects

No information available

### Other Information

Do not dispose of this product in drains, watercourses, or on the ground.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product residues are classified as chemical waste.

**Category of waste:** Waste-code: 08 01 11 Waste paint and varnish containing organic solvents or other dangerous substances

## SECTION 14: Transport information

<b>14.1. UN-No.:</b>	Not applicable.	<b>14.4. Packing group:</b>	Not applicable.
<b>14.2. UN proper shipping name:</b>	Not applicable.	<b>14.5. Environmental hazards:</b>	Not applicable.
<b>14.3. Transport hazard class(es):</b>	Not applicable.		

### 14.6. Special precautions for user

Irrelevant.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Irrelevant.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Esbjerg Farve- & Lakfabrik A/S, Energivej 13, DK-6700 Esbjerg, www.esbjergpaints.dk

8 / 9

# Safety Data Sheet

## FAXE Maintenance Oil 0245

Replaces date: 27/03/2015

Revision date: 03/07/2015  
Version: 4.0.0

### 15.2. Chemical Safety Assessment

**Other Information:** Chemical safety assessment has not been performed.

### SECTION 16: Other information

#### Version history and indication of changes

Version	Revision date	Responsible	Changes
1.0.0	17/06/2013	GK	
2.0.0	24/10/2013	GK	2, 7, 8, 9, 12, 15, 16
3.0.0	14/03/2014	GK	1
4.0.0	27/03/2015	GK	2, 3, 8, 11, 12

**Abbreviations:** DNEL: Derived No Effect Level. PNEC: Predicted No Effect Concentration.

**References to literature and data sources:** REACH: REGULATION OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals. DPD: Directive of the European Parliament and of the Council concerning the approximation of the laws, regulations and administrative provisions of the Member States relating to the classification, packaging and labelling of dangerous preparations. CLP: REGULATION OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on classification, labelling and packaging of substances and mixtures.

**Other Information:** The information in this Material Safety Data Sheet is based upon our knowledge and on European Union legislation. The user's working conditions are outside our control. It is the responsibility of the users to fulfil the requirements set by National Legislation. The information is no guarantee of the properties of the product. The Material Safety Data Sheet may only be reproduced with the permission of the manufacturer.

**Training advice:** The instructions in this Material Safety Data Sheet are given on the assumption that the product is used as stated in item 1. Restrictions of use and special training requirements must also be complied with. The information in this Material Safety Data Sheet should be regarded as a description of the safety issues concerning the product.

#### List of relevant H-statements

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H361d Suspected of damaging the unborn child.  
H413 May cause long lasting harmful effects to aquatic life.

**Document language:** GB